

Waterhog™ Eco Premier #2295

Entrance Mat – 10mm thick

Features and Benefits

- Waterhog™ Eco Premier has a ridged construction that effectively removes and traps dirt and moisture below shoe level.
- Exclusive rubber-reinforced face nubs prevent pile from crushing, maintaining high performance and extending product life.
- Premium tri-denier polypropylene fibre system allows fabric to dry quickly while preventing fading and rotting.
- 50% heavier than Waterhog™ Classic.
- Anti-static rating averaging 1.2KV with a maximum average voltage of 1.6KV as measured by the AATCC.
- Green friendly rubber backing has 20% recycled rubber content.
- All Waterhog mats are certified slip resistant by the National Floor Safety Institute
- Tested by CSIRO.



Construction Details

A: Unique ridged construction effectively removes and traps dirt and moisture beneath shoe level.

B: Exclusive rubber-reinforced face nubs prevent pile from crushing, maintaining high performance extending product life.

C: Premium polypropylene allows fabric to dry quickly and prevents fading and rotting. Mats can easily be vacuumed or hosed out.

D: Special gripper rubber backing minimises movement on carpets or hard surfaces.

E: Exclusive "water dam" allows Waterhog™ Eco Premier to trap dirt and water so they stay in the mat and off your floor - minimising slip hazards and floor damage around the perimeter of the mat.

Note: Colours subject to change from dye lot to dye lot.

Specifications

Uses: Entrance areas

Compound: Yarn: Solution-dyed polypropylene, Backing: SBR Rubber

Durometer: 55 per ASTM D2240

Thickness: 10mm

Edges: Safety bevelled on all four sides

Flammability: "A" Rating of DOC FF1-70

Warranty: 3 years

Colour: Indigo, Southern Pine, Black Smoke



Mat Stock Sizes*

580mm x 900mm

900mm x 1500mm

1150mm x 1780mm