

Richard Pieris Exports PLC No 10, Raja Mawatha, Ekala, Ja-Ela, Sri Lanka Tel. +94 114834150

Product Specification Sheet

Product code:	MSE47SSBK
Name:	ElectricalShockProof
Country of origin:	Sri Lanka
Material:	Made out of 100% Natural rubber and other approved
	rubber chemicals use in rubber industry.
Size:	1000 x 1000 mm (± 10 mm)
Weights:	$9.250 \pm 0.200 \text{ kg}$
Thickness:	$6.5 \pm 0.5 \text{ mm}$
Colours:	Black
Packaging:	Approx. 175 - mats per pallet
Safety:	Anti fatigue slip resistant rubber mat
Temperature Resistance:	-30 to +50 °C
Electrical Resistance:	According to AS/NZS 2978: 1995(Insulating mats for electrical purpose),
	leakage current is less than 160 mA/m ² for any position of the electrodes.
Slip Resistance	30 BPN, According to ASTM E303
Markings	The number of Standard
	The date of manufacture'
	The name or identification mark of manufacture,
	The words '450 V maximum'.
Maintenance:	Use a high pressure hose(not exceed 60psi) to remove the dirt
	and debris on the mats.
	For best results use a mild detergent (pH 4.0-9.0) to clean the mats.
	Do not use steam, degreasers or caustic chemicals.
	Do not mechanically scrub the mats.
Recommended:	Use as floor coverings near electrical apparatus where
	circumstances involve the possibility of direct contact
	with conductors whose voltage does not exceed 450 V
	r.m.s. to earth. This mat does not resist to oils & greases.
Recycle:	Yes.